

## PIT m3.2p

402230



PITmode electronic selector switch for control panel installation and for safe selection of 5 operating modes via a non-contact key and selection of buttons.

## Dane

|                    |                            |
|--------------------|----------------------------|
| Certyfikacja:      | CE;cULus Listed;TÜV;FCC;IC |
| Szerokość:         | 98.0 mm                    |
| Wysokość:          | 55.0 mm                    |
| Głębokość:         | 43.0 mm                    |
| Ciężar brutto:     | 260 g                      |
| Ciężar netto:      | 140 g                      |
| Temperatura pracy: | -20 - 60 °C                |

## Akcesoria



402302

PIT m3.2p terminal set spring load



402303

PIT m3.2p screw terminal set angled



402305

PIT m3.2p screw terminal set

|                                                                                     |        |                            |
|-------------------------------------------------------------------------------------|--------|----------------------------|
|    | 402281 | PIT m3 key2 mode 1         |
|    | 402284 | PIT m3 key2 mode 4         |
|    | 402292 | PIT m3 key2hq mode 2       |
|   | 402291 | PIT m3 key2hq mode 1       |
|  | 402282 | PIT m3 key2 mode 2         |
|  | 402283 | PIT m3 key2 mode 3         |
|  | 402295 | PIT m3 key2hq mode service |
|  | 402293 | PIT m3 key2hq mode 3       |
|  | 402294 | PIT m3 key2hq mode 4       |



402285

PIT m3 key2 mode service

---