

PSEN sl-0.5p 4.1

570578



Safety gate system with magnetic interlock, IP67, 8pin M12 connector (male). 2 safe semiconductor outputs (OSSD); Solenoid power 500N (process guarding); 4 LEDs; Applications up to SIL3/PL e/Cat4; additional function: safe semiconductor outputs are high if door is closed (independent from guardlocking function); Content = 1 fully coded Sensor without actuator. Teach-in of new actuators up to 8 times.

Dane

Zapewniony odstęp wyłączenia:	15.0 mm
Certyfikacja:	CE;cULus Listed;EAC (Eurasian);TÜV;FCC;IC
Zasada działania czujnika:	Transponder
Rodzaj kodowania:	W pełni kodowany
Siła trzymania:	500 N
Liczba wyjść OSSD:	2
Liczba wejść:	3
Rodzaj przyłącza:	M12, 8pol. male
Napięcie zasilania (V):	24,0
Rodzaj napięcia zasilania:	DC
Pobór mocy DC:	4.8 W
Stopień ochrony obudowy:	IP67
Szerokość:	45.0 mm
Wysokość:	122.0 mm
Głębokość:	44.0 mm
Ciężar brutto:	630 g
Ciężar netto:	570 g
Temperatura pracy:	-25 - 55 °C

Akcesoria



570521

PSEN sl-0.5 2.1 1actuator

Akcesoria opcjonalne



540319

PSEN cable axial M12 8-pole 3m



540320

PSEN cable axial M12 8-pole 5m



540321

PSEN cable axial M12 8-pole 10m



540322

PSEN cable angle M12 8-pole 3m



540323

PSEN cable angle M12 8-pole 5m



540324

PSEN cable angle M12 8-pole 10m



540325

PSEN cable angle M12 8-pole 30m



540326

PSEN cable axial M12 8-pole 30m



540328

PSEN Y junction M12-M12/M12



570550

PSEN sl bracket swing door



570551

PSEN sl bracket sliding door



540331

PSEN T junction (auxiliary contact) M12



773603

PDP67 F 4 code



540312

PSEN screw M5x20 10pcs



540340

PSEN cable M12-8sf M12-8sm, 2m



540341

PSEN cable M12-8sf M12-8sm, 5m



540343

PSEN cable M12-8sf M12-8sm, 20m



540344

PSEN cable M12-8sf M12-8sm, 30m



540342

PSEN cable M12-8sf M12-8sm, 10m



540333

PSEN cable M12-8sf, 20m